

How To Set Up the WorkCentre 92xx (ColorQube) for EIP

Prerequisites:

- The WorkCentre must have the latest firmware installed. You can download the firmware from the Xerox website.
- The Device must be EIP-capable.

Settings for the WorkCentre 9200 Series

You use the CentreWare Internet Services interface to the MFP to configure the device settings.

CentreWare – in website set <http://ip-mfp> (example <http://192.168.0.61>)

When accessing CentreWare Internet Services, a login page may display prompting for a username and password. If you do not know the password, contact your administrator. The default password is 1111. If the administrator encounters a problem changing the password, or forgets the password, a service call must be placed.

1. Configure **Machine Digital Certificate** by doing the following:
 - a. Click the **Index** link located in the upper-right hand corner of the page.
 - b. Click the **Extensible Service Setup** Link.
 - c. On the Extensible Service Setup page under the **Setup (Required)** heading, click the **Configure...** or **Edit...** button next to **HTTP (SSL)**.
 - d. On the HTTP page, click the **Configure Machine Digital Certificate** link located at the bottom of the page. (In a yellow box)
 - e. On the Machine Digital Certificate Management page, click the **Create New Certificate** button.
 - f. Under the Create New Certificate heading, select **Self Signed Certificate**.
 - g. Click the **Continue** button and enter the required information.
 - h. Click the **Apply** button.
2. Enable **HTTP (SSL)** by doing the following:
 - a. Click the **Index** link located in the upper-right hand corner of the page.
 - b. Click the **Extensible Service Setup** link.
 - c. On the Extensible Service Setup page under the **Setup (Required)**, click the **Configure...** or **Edit...** button next to **HTTP (SSL)**.
 - d. On the HTTP page, select **Enabled** in the configuration area under the **Secure HTTP (SSL)**.
 - e. Click the **Save** button
3. Configure the **Extensible Service Registration** by doing the following:
 - a. Click on the **Index** link located in the upper-right hand corner of the page.
 - b. Click the **Extensible Service Setup** link.
 - c. On the Extensible Service Setup page under the **Setup (Required)**, click the **Configure...** or **Edit...** button next to **Extensible Service Registration**.
 - d. On the HTTP Web Services page, configure the following settings:
 - **Extensible Service Registration:** Enabled
 - **Scan Template Management:** Enabled
 - **Session Data:** Enabled
 - **Scan Extension:** Enabled
 - **Device Configuration:** Enabled
 - e. Click the **Save** button